-	19.00-	- - ·	46
	19 Image: Controls Breaker Controls Breaker Image: Controls Breaker Image:		
	FRONT VIEW		
	17.28		
		O	

D

С

В

$(\mathcal{A}) (\mathcal{A}) $	2
<u>REAR VIEW</u>	

Configuration	Features	VMtr, AMtr, Seq, Srg	Physical	Dimensions	1 U x 19" W x 9" D	
	Layout	10		Weight	lbs	
				Materials	Chassis: Steel	
Input 1	Voltage	100-240 Vac, Single Phase, 50/60 Hz		Finishes	Chassis: Zinc plated Black,	
	Max Current	20 Amps				
	Max Load	3.84 KVA	Operating	Temperature	32°F to 122°F	
				Humidity	5 %RH to 85 %RH	
	Connection	C20		Elevation	25,000 feet	
	Voltage Monitor	Digital, ±1% Full Scale				
	Current Monitor	Digital, ±1% Full Scale	Conformance	Warranty	http://www.marway.com/	
				Safety Certifications	None	
Outlets	All Panels [1][2]	(1) C13, 100-240V		Environment Certifications	None	
		(8) C13, 100-240V (S)				
			Notes:			
Protection	Spike/Surge Suppression [1]	Yes	[1] Certain details	of the circuitry may only be revea	led by the schematic (availab	
	EMI Filter [1]	None	[2] S = switched, V = monitored voltage, A = monitored amps			
	Over Current [1]	(1) 20A Main Breaker				
Env Sensors	Temperature	2				
	Humidity	2				
	Interlocks	None				
	EPO	None			UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MILLIMETERS] TOLERANCES ARE:	
Communications	Display	Multi-function Controller			ANGLES DECIMALS #.5' JXX #.03 DO NOT SOLE DRAWING	
	Serial	RS-232 (RJ-45)			MATERIAL: DO NOT MATERIAL: DRAWING DRAW	
	Ethernet	10T/100T Auto			CHE	
	Protocols	HTTP, HTTPS, Telnet, SSH, FTP, SMTP, SNMPv2, SNMPv3, SNTP, AlertLog			APP FINISH:	

А

-8.92-

⊗

⊗

