

<u>REAR VIEW</u>

Configuration	Features	Seq, Srg	Physical	Dimensions	1 U x 1
	Layout	10		Weight	lbs
				Materials	Chassi
Input 1	Voltage	120 Vac, Single Phase, 50/60 Hz		Finishes	Chassi
	Max Current	30 Amps			
	Max Load	2.88 KVA	Operating	Temperature	32°F to
				Humidity	5 %RH
	Connection	L5-30P, 9 ft cord, 3-wire 10 ga, SJT jacket (Rear panel)		Elevation	25,000
	Voltage Monitor	None			
	Current Monitor	None	Conformance	Warranty	http://
				Safety Certifications	None
Outlets	All Panels [1][2]	(1) 5-20R, 120V		Environment Certifications	None
		(8) 5-20R, 120V (S)			
			Notes:		
Protection	Spike/Surge Suppression [1]	Yes	[1] Certain detai	Is of the circuitry may only be reve	aled by th
	EMI Filter [1]	None	[2] S = switched,	V = monitored voltage, A = monitor	ored amps
	Over Current [1]	(2) 20A Circuit Breaker			
Env Sensors	Temperature	2			
	Humidity	2			
	Interlocks	None			
	EPO	None			UNLE: DIMENSION ANG ± .
Communications	Display	None			
	Serial	RS-232 (RJ-45)			
	Ethernet	10T/100T Auto			
	Protocols	HTTP, HTTPS, Telnet, SSH, FTP, SMTP, SNMPv2, SNMPv3, SNTP, AlertLog			FINISH:

А

D

С

В

8

6

7

5

4

3

1 U x 19" W x 9" D

Chassis: Steel

32°F to 122°F 5 %RH to 85 %RH 25,000 feet

UNLESS OTHERWISE SPECIFIED INSIONS ARE IN INCHES [MILLI

ANGLES

DECIMALS .XX ± .03 .XXX ± .010

