

Configuration	Features	EMI, Srg		
	Layout	1 U		
Input 1	Voltage	100-240 Vac, Single Phase, 50/60 Hz		
	Max Current	30 Amps		
	Max Load	5.76 KVA		
	Connection	L6-30P, 9 ft cord, 3-wire 10 ga, SJT jacket (Rear panel)		
	Voltage Monitor	None		
	Current Monitor	None		
Outlets	All Panels [1][2]	(12) C13, 100-240V		
		(4) C19, 100-240V		
Protection	Spike/Surge Suppression [1]	Yes		
	EMI Filter [1]	Yes		
	Over Current [1]	(2) 20A Circuit Breaker		
Env Sensors	Temperature	None		
	Humidity	None		
	Interlocks	None		
	EPO	None		
Communications	Display	None		
	Serial	None		
	Ethernet	None		
	Protocols	None		

REAR VIEW

Physical	Dimensions	1 U x 19" W x 8" D	
	Materials	Chassis: Steel	
	Finishes	Chassis: Painted Black, F	
Operating	Temperature	32°F to 122°F	
	Humidity	5 %RH to 85 %RH	
	Elevation	6,562 feet	
Conformance	Warranty	http://www.marway.co	
	Safety Certifications	UL, CUL, CE, RoHS	
	Environment Certifications	None	
Notes:			
[1] Certain detail	ls of the circuitry may only be rev	vealed by the schematic (a	
[2] S = switched,	V = monitored voltage, A = moni	tored amps	

4

UNLESS OTHERM DIMENSIONS ARE IN I TOLERANC ANGLES ± .5°		NCHES [MILLIMETERS	
	₽	DO NOT SCALE DRAW	ING
MATERIAL			
FINISH:			
٦			

8

D

С

В

А

6

7

5

