

Configuration	Features	Seq, Srg	Physical	Dimensions
	Layout	Zero U		Weight
				Materials
Input 1	Voltage	100-120 Vac, Single Phase, 50/60 Hz		Finishes
	Max Current	15 Amps		
	Max Load	1.44 KVA	Operating	Temperature
				Humidity
	Connection	5-15P, 14 ft cord, 3-wire 14 ga, SJT jacket (Front panel)		Elevation
	Voltage Monitor	None		
	Current Monitor	None	Conformance	Warranty
				Safety Certifi
Outlets	All Panels [1][2]	(24) 5-15R, 100-120V (S)		Environment
Protection	Spike/Surge Suppression [1]	Yes	Notes:	
	EMI Filter [1]	None	[1] Certain details of the circuitry may	
	Over Current [1]	(1) 15A Main Breaker	[2] S = switched, V = monitored voltage	
Env Sensors	Temperature	2		
	Humidity	2		
	Interlocks	None		
	EPO	None		
Communications	Display	None		
	Serial	RS-232 (RJ-45)		
	Ethernet	10T/100T Auto		
	Protocols	AlertLog, HTTP, HTTPS, Telnet, SSH, FTP, SMTP, SNMPv2, SNMPv3, SNTP		

Physical	Dimensions	72" H x 2.5" W x 3.5" D
	Weight	lbs
	Materials	Chassis: Steel
	Finishes	Chassis: Zinc plated Blac
Operating	Temperature	32°F to 122°F
	Humidity	5 %RH to 85 %RH
	Elevation	25,000 feet
Conformance	Warranty	http://www.marway.co
	Safety Certifications	None
	Environment Certifications	None
Notes:		
[1] Certain details of th	ne circuitry may only be revealed	by the schematic (availa
[2] S = switched V = m	onitored voltage. A = monitored	amps

3

А